



PACKAGES

Available options to prevent air leaks and reduce energy costs

Weather stripping

Sealed edge & double wall door

Meets the ENERGY STAR requirements

ENERGY-SAVER R-3 *Standard on the Titan*

- 1 3/4" thick, R-3.5 R-max® aluminum foil faced insulation panel
- 1 3 piece 1x4 Door Frame constructed with 100% Nuts & Bolts
- 1 Withstands temperatures of up to 275° F
- 1 Fire Treated option on all Energy-Saver options



ENERGY-SAVER R-5

- 1 Certified R-5 door system utilizing a R-max® R-5 3/4" foil-faced insulation panel
- 1 Bulb type weather stripping
- 1 Meets or exceeds the Energy Code requirements for many states
- 1 Hardboard Cover over insulation



ENERGY PERFORMANCE RATINGS	
U-Factor (U.S./I-P)	Overall Stabilized R-Value of 72
0.20	R-5

ENERGY-SAVER R-10

- 1 Certified R-10 door system utilizing a R-max® R-13.1 2" foil faced insulation panel
- 1 Bulb type weather stripping
- 1 Meets or Exceeds the Energy Code requirements for many states
- 1 Meets ENERGY STAR® qualified homes requirements
- 1 Hardboard cover over insulation



ENERGY PERFORMANCE RATINGS	
U-Factor (U.S./I-P)	Solar Heat Gain Coefficient
0.10	0.01

THERMABLOC®

- 1 The industry's first thermal barrier attic door
- 1 Maintains the integrity of a ceiling's thermal envelope
- 1 Certified R-10 door system utilizing a R-max® R-13.1 2" foil faced insulation panel
- 1 Q-Lon Smoke Rated Weather-Stripping
- 1 Helps to meet LEED Home credit categories

